

Fuji USER MANUAL

SCREW DRIVERS

(IMPACT CLUTCH TYPE)



MODELS : FW-5SXD-7, -70, -8, -80



FW-5SXD-7, -70



FW-5SXD-8, -80

Bit Size	Size	Model
	(A) 9.5mm	FW-5SXD-7, -8
	(B) 12 mm	
	(A) 13 mm	FW-5SXD-70, -80
	(B) 16 mm	

SPECIFICATIONS

Model	Capacity Screw Size (Guidance)		Rotational Frequency	Distance from Center to Side		Bit Shank Size		Overall Length (without socket)		Mass		Air Consumption (At Load)		Air Inlet Thread Size	Air Hose Size	
	mm	in		mm	in	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min		mm	in
FW-5SXD-7, -70	5	3/16	12,000	17.0	43/64	6.35	1/4	223	8 25/32	0.70	1.5	0.20	7.1	PT or NPT 1/4	6.3	1/4
FW-5SXD-8, -80	5	3/16	12,000	17.0	43/64	6.35	1/4	193	7 19/32	0.65	1.4	0.20	7.1	PT or NPT 1/4	6.3	1/4

The performance figures are at 0.63MPa (6.3bar).

 Refer to "The Instructions and Warning for Safety Use" enclosed in each tool box.

Fuji Industrial Technique Co.,Ltd.

2-1-14, Kamiji, Higashinari-ku, Osaka, 537-0003 Japan

Tel : 81-6-6972-2335

Fax : 81-6-6972-2380

